

EXPLANATION OF TABLES IN APPENDIX I

LOCATION	MAT'L CODE	MATERIAL IDENTIFICATION	ASBESTOS CONTENT (%/Type)	REFERENCE SAMPLE NUMBER	QUANTITY	<u>UNIT</u>	<u>PHYSICAL ASSESSMENT</u>	
						Lin Ft. Sq. Ft. Each	FRI	CON
Room 1	T	<4" white fibrous PI	20% chrys	1	15	LF	F	L
Room 2		NSMP						

LOCATION= The room or functional space in the building where a given material exists.

MATERIAL CODE= Each suspect material is listed as one of the following:

T= thermal system insulation

S= surfacing materials

M= miscellaneous materials

NSMP=no suspect materials present

MATERIAL IDENTIFICATION= A brief verbal description of the material in question. Pipe insulation is denoted as **PI**. Pipe fitting insulation, such as pipe elbow, valve or fitting insulation is denoted as **PFI**.

ASBESTOS CONTENT (%/Type)= The amount and type of asbestos found to be present in a given material based on laboratory analysis.

N.D. =no asbestos fibers detected in the samples of the identified material.

REFERENCE SAMPLE NUMBER= The number assigned to a given homogeneous material for sampling and tracking purposes.

QUANTITY= The amount of a given identified material within the room or functional space.

This material can be identified by verbal description or reference sample number.

UNITS=The units by which the suspect material was quantified as indicated below:

LF=linear feet

SF= square feet

EA=each

PHYSICAL ASSESSMENT= The condition of the identified material is described in terms of friability (**FRI**) or nonfriability:

F= friable material

N= nonfriable material

and in terms of actual condition (**CON**) found during the time of the building survey as indicated in the following:

N=no damage

L=<10% (Little) damage

M=10-25% (Moderate) damage

H= >25% (Heavy) damage